

### Ⓢ Squeeze Connector Greenfield Straight

**Standard:** UL 514B and C22.2 No. 18.3-12

**Material:** Zinc

**Application:** for use to bond flexible metal conduit or armored cable to a box or enclosure



TOPELE#	Trade Size	Shelf QTY	Master QTY	Dim A (inch)	Dim B (inch)
SCN-12	3/8"	100	1000	1.000	0.58~0.62
SCN-15	1/2"	50	500	1.468	0.74~0.95
SCN-20	3/4"	25	250	1.581	0.88~1.12
SCN-25	1"	20	200	1.750	1.14~1.38
SCN-32	1-1/4"	*	200	1.912	1.42~1.65
SCN-38	1-1/2"	*	100	2.090	1.68~1.95
SCN-50	2"	*	100	2.341	2.08~2.56
SCN-60	2-1/2"	*	25	2.811	2.85~3.25
SCN-70	3"	*	20	3.840	3.33~3.65
SCN-80	4"	*	10	4.562	4.18~4.58

### Ⓢ Squeeze Connector Greenfield 90°

**Standard:** UL 514B and C22.2 No. 18.3-12

**Material:** Zinc

**Application:** for use to bond flexible metal conduit or armored cable to a box or enclosure



TOPELE#	Trade Size	Shelf QTY	Master QTY	Dim A (inch)	Dim B (inch)
SACN-25	3/8"	50	500	1.740	0.43~0.69
SACN-50	1/2"	30	300	2.110	0.64~0.98
SACN-75	3/4"	20	200	2.400	0.76~1.12
SACN-100	1"	10	100	2.870	1.08~1.68
SACN-125	1-1/4"	*	80	4.000	1.35~1.85
SACN-150	1-1/2"	*	30	6.000	1.56~2.54
SACN-200	2"	*	30	6.000	1.68~2.56
SACN-250	2-1/2"	*	10	7.187	2.45~2.95
SACN-300	3"	*	10	7.875	2.95~3.35
SACN-400	4"	*	5	10.200	3.75~4.45

### Ⓢ "U" Shaped Connector

**Material:** Steel

**Application:** for use with armored cable and flexible metal conduit



TOPELE#	Trade Size	Shelf QTY	Master QTY	Dim A(inch)	Dim B (inch)
P2	1/2"	25	250	1.380	1.249
P3	3/4"	20	200	1.382	1.438
P4	1"	12	120	1.558	1.807

### Ⓢ EMT to Flex Coupling

**Standard:** UL 514B and C22.2 No. 18.3-12

**Material:** Zinc

**Application:** for use to couple EMT to flexible metal conduit or armored cable



TOPELE#	Trade Size	Shelf QTY	Master QTY	Dim A (inch)	Dim B (inch)
EF-25	1/2"--3/8"	50	500	1.260	0.58~0.62
EF-50	1/2"	30	300	1.520	0.74~0.95
EF-75	3/4"	20	200	1.830	0.88~1.12
EF-100	1"	20	200	1.970	1.14~1.38

### Ⓢ Interior Flex Connector

**Standard:** UL 514B and C22.2 No. 18.3-12

**Material:** Zinc

**Application:** for use to bond flexible metal conduit to a box or enclosure



TOPELE#	Trade Size	Shelf QTY	Master QTY	Dim A (inch)	Dim B (inch)
IFC-25	3/8"	150	1500	1.035	0.484
IFC-50	1/2"	100	1000	1.118	0.610
IFC-75	3/4"	50	500	1.248	0.815
IFC-100	1"	30	300	1.366	0.965

### Ⓢ Romex Connector for Nonmetallic Cable

**Standard:** UL 514B and C22.2 No. 18.3-12

**Material:** Zinc

**Application:** for use to bond nonmetallic cable to a box or enclosure



TOPELE#	Trade Size	Shelf QTY	Master QTY	Dim A (inch)	Dim B (inch)
RCN-25	3/8"	100	1000	0.825	0.421
RCN-50	1/2"	100	1000	0.825	0.421
RCN-75	3/4"	50	500	1.000	0.482
RCN-100	1"	25	250	1.285	0.780
RCN-125	1-1/4"	25	250	1.312	0.710
RCN-150	1-1/2"	15	150	1.453	0.817
RCN-200	2"	10	100	1.590	0.823