

Female Flexible Conduit Connector-Zinc

typeA



CAT#	SIZE
DPN-15	1/2"
DPN-20	3/4"
DPN-25	1"
DPN-32	1"
DPN-38	1-1/4"
DPN-50	1-1/2"
DPN-64	2"
DPN-75	2-1/2"
DPN-100	3"

typeB



Flex Conduit Compression Connector-Zinc

typeA



CAT#	SIZE
DGJ-15/FF/TT	1/2"
DGJ-20/FF/TT	3/4"
DGJ-25/FF/TT	1"
DGJ-32/FF/TT	1-1/4"
DGJ-38/FF/TT	1-1/2"
DGJ-50/FF/TT	2"
DGJ-64/FF/TT	2-1/2"
DGJ-75/FF/TT	3"
DGJ-100/FF/TT	4"

typeB



Liquid Tight Non-Metallic Flexible Conduit

Temperature : -18°C~+80°C Dry, 60°C Wet, 70°C Oil

IP68, Grey

Flexibility : Medium

Fire Retardant : Self-extinguishing

UV Resistance : Yes



TOPELE#	Size	I.D.(mm)		O.D.(mm)		Bending Radius (mm)	Packing (m)
NMLTFC-38	3/8"	12.29	12.80	17.53	18.03	51	50
NMLTFC-50	1/2"	15.80	16.31	20.83	21.34	82.5	50
NMLTFC-75	3/4"	20.83	21.34	26.16	26.67	108	40
NMLTFC-100	1"	26.44	27.08	32.77	33.40	165	30
NMLTFC-125	1-1/4"	35.05	35.81	41.40	42.16	203	30
NMLTFC-150	1-1/2"	40.01	40.64	47.37	48.26	228.5	20
NMLTFC-200	2"	51.31	51.94	59.44	60.33	282	10

Non-Metallic Flexible Conduit Connector

Temperature Range : Medium

IP Rating : IP 68

Fire Retardant : Self-extinguishing

Certificate : cULus

Plum Type Male Flexible Conduit Connector-Zinc



CAT#	SIZE
MPJ-15	1/2"
MPJ-20	3/4"
MPJ-25	1"
MPJ-32	1-1/4"
MPJ-38	1-1/2"
MPJ-50	2"
MPJ-64	2-1/2"
MPJ-75	3"
MPJ-100	4"



Plum Type Flexible Conduit Coupling-Zinc



CAT#	SIZE
MKJ-15	1/2"
MKJ-20	3/4"
MKJ-25	1"
MKJ-32	1-1/4"
MKJ-38	1-1/2"
MKJ-50	2"
MKJ-64	2-1/2"
MKJ-75	3"
MKJ-100	4"



90° Flexible Conduit Connector-Zinc

typeA



CAT#	SIZE
DWJ-15	1/2"
DWJ-20	3/4"
DWJ-25	1"
DWJ-32	1-1/4"
DWJ-38	1-1/2"
DWJ-50	2"
DWJ-64	2-1/2"
DWJ-75	3"
DWJ-100	4"

typeB



45° Flexible Conduit Connector-Zinc



CAT#	SIZE
DNJ-15	1/2"
DNJ-20	3/4"
DNJ-25	1"
DNJ-32	1-1/4"
DNJ-38	1-1/2"
DNJ-50	2"
DNJ-64	2-1/2"
DNJ-75	3"
DNJ-100	4"



typeA



Straight

CAT#	SIZE
NMCS-38	3/8"
NMCS-50	1/2"
NMCS-75	3/4"
NMCS-100	1"
NMCS-125	1-1/4"
NMCS-150	1-1/2"
NMCS-200	2"

typeB



typeA



90° Angle

CAT#	SIZE
NMCA-38	1/2"
NMCA-50	1/2"
NMCA-75	3/4"
NMCA-100	1"
NMCA-125	1-1/4"
NMCA-150	1-1/2"
NMCA-200	2"

typeB

